
Antennas GPS-703-GGG



HIGH PERFORMANCE PINWHEEL® TRIPLE-FREQUENCY ANTENNA MAXIMIZES TRACKING CAPABILITIES



MAXIMIZE PERFORMANCE WITH MULTI-CONSTELLATION RECEPTION

The GPS-703-GGG receives L1, L2, L5 GPS; L1, L2, L3 GLONASS; B1, B2 BeiDou and E1, E5a/b Galileo frequencies. Customers can use the same antenna for GPS-only, dual or triple constellation applications, resulting in increased flexibility and reduced equipment costs.

STABLE PHASE CENTER

The phase center of this antenna remains constant as the azimuth and elevation angle of the satellites change. Signal reception is unaffected by the rotation of the antenna or satellite elevation, so placement and installation of the antenna can be completed with ease. With the phase center in the same location for the GNSS signals and with minimal phase center variation between antennas, this antenna is ideal for baselines of any length.

DURABLE, FUTURE-PROOF DESIGN

This rugged antenna is enclosed in a durable, waterproof housing and meets MIL-STD-810G for vibration and salt spray. While the GPS-703-GGG-HV has a similar form-factor to our high performance GPS-700 antenna series, it offers increased robustness for use under high vibration conditions.

Meeting the European Union's directive for Restriction of Hazardous Substances (RoHS), integrators can be confident the GPS-703-GGG antenna can be used in system designs for years to come.

BENEFITS

- + Choke ring antenna functionality without the size and weight
- + Reduces equipment costs and need for future redesign
- + High quality measurements and stable phase center for precision applications

FEATURES

- + L1, L2, L3, L5, B1, B2, E1 and E5a/b
- + GPS+GLONASS+BeiDou+Galileo signal reception
- + Excellent multipath rejection
- + Highly stable phase center
- + RoHS compliant

If you require more information about our antennas, visit www.novatel.com/antennas

GPS-703-GGG

PERFORMANCE

3 dB Pass Band

L1/B1/E1	1580.0 ± 28.5 MHz (typical)
L2/L3/L5/B2/E5/E5a/E5b	1210.0 ± 45.0 MHz (typical)

Out-of-Band Rejection

L1 ± 100 MHz	30 dBc (typical)
L2 ± 200 MHz	50 dBc (typical)

LNA Gain

29 dB (typical)

Gain at Zenith (90°)

GPS L1	+5.0 dBic (minimum)
GPS L2	+3.0 dBic (minimum)
GPS L5	+3.0 dBic (minimum)

Gain Roll-Off (from Zenith to Horizon)

GPS L1	12 dB
GPS L2	13 dB
GPS L5	13 dB

Noise Figure 2.0 dB (typical)

VSWR ≤2.0 : 1

L1-L2 Differential Propagation Delay
5 ns (maximum)

Nominal Impedance 50 Ω

Altitude 9,000 m

PHYSICAL AND ELECTRICAL

Dimensions 185 mm diameter¹ × 69 mm

Weight 500 g

Power

Input voltage +4.5 to +18.0 VDC

Current 36 mA (typical)

Connectors TNC female

Optional N-Type

ENVIRONMENTAL

Temperature

Operating -40°C to +85°C

Storage -55°C to +85°C

Humidity 95% non-condensing

Vibration (operating)

Random MIL-STD-810G 514.6E-1
Category 24

Sinusoidal
ASAE EP455 Section 5.15.2 Level 1
ISO 9022-3 Method 36

Shock IEC 68-2-27 Ea

Bump IEC 68-2-29 (Eb)

Salt Spray MIL-STD-810G 509.5

Waterproof IPX6/IPX7

Compliance FCC, CE

RoHS EU Directive 2011/65/EU

For the most recent details of this product:

www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas/gps-703-ggg/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 9 Specifications subject to change without notice.

©2015 NovAtel Inc. All rights reserved.

NovAtel and Pinwheel are registered trademarks of NovAtel Inc.

Printed in Canada.

D13878 November 2015



1. Not including tape measure tab. Full diameter with tape measure tab is 195 mm.

