

# Antennas GPS-713-GGG-N & GPS-713-GGGL-N



ATEX QUALIFIED, PINWHEEL®  
TRIPLE-FREQUENCY ANTENNA,  
WITH INMARSAT REJECTION FILTER,  
MAXIMIZES TRACKING CAPABILITIES



## MAXIMIZE PERFORMANCE WITH MULTI-CONSTELLATION RECEPTION

The GPS-713-GGG-N and GPS-713-GGGL-N receives L1, L2, L5 GPS; L1, L2, L3 GLONASS; B1, B2 BeiDou and E1, E5a/b Galileo frequencies. The GPS-713-GGGL-N also supports L-Band from 1525 to 1560 MHz. Customers can use the same antenna for GPS-only, dual or triple constellation applications, resulting in increased flexibility and reduced equipment costs. Both antennas provide enhanced Inmarsat interference rejection, which allows tracking of GNSS signals in the presence of high powered Inmarsat transmitters typically found on marine vessels.

## STABLE PHASE CENTER

The phase center of this antenna remains constant as the azimuth and elevation angle of the satellites change. Signal reception is unaffected by the rotation of the antenna or satellite elevation, so placement and installation of the antenna can be completed with ease. With the phase center in the same location for the GNSS signals and with minimal phase center variation between antennas, this antenna is ideal for baselines of any length.

## DURABLE, FUTURE-PROOF DESIGN


This rugged antenna is enclosed in a durable, waterproof housing and meets MIL-STD-810G for vibration, corrosive environment and salt fog. The GPS-713-GGG-N and GPS-713-GGGL-N are similar in form factor to our other high performance GPS-700 series antennas. Both antennas meet IEC60945 specifications.

Meeting the European Union's directive for Restriction of Hazardous Substances (RoHS), integrators can be confident the GPS-713-GGG-N and GPS-713-GGGL-N antennas can be used in system designs for years to come.

## BENEFITS

- + Choke ring antenna functionality without the size and weight
- + Reduces equipment costs and need for future redesign
- + High quality measurements and stable phase center for precision applications
- + GNSS reception even in the presence of Inmarsat transmitters

## FEATURES

- + L1, L2, L3, L5, B1, B2, E1, E5 and E5a/b
- + GPS+GLONASS+BeiDou+Galileo signal reception
- + Increased Inmarsat rejection
- + Excellent multipath rejection
- + Highly stable phase center
- + RoHS compliant
- + REACH compliant
- +  II 3 G Ex ic IIC T4 Gc X

If you require more information about our antennas, visit [www.novatel.com/antennas](http://www.novatel.com/antennas)

# GPS-713-GGG-N & GPS-713-GGGL-N

## PERFORMANCE

### 3 dB Pass Band

Upper Band:	1568 ± 43 MHz (-GGGL) 1584 ± 27 MHz (-GGG)
Lower Band:	1210 ± 45 MHz (both variants)

### Out-of-Band Rejection

GGGL variant	
L1 ± 100 MHz / 30 dB (minimum)	
L1 ± 150 MHz / 50 dB (minimum)	
L2 ± 100 MHz / 30 dB (minimum)	
L2 ± 150 MHz / 50 dB (minimum)	
Inmarsat immunity	45 dB (minimum)

### GGG variant

L1 ± 84 MHz / 30 dBc (minimum)	
L1 ± 134 MHz / 50 dBc (minimum)	
L2 ± 100 MHz / 30 dBc (minimum)	
L2 ± 150 MHz / 50 dBc (minimum)	
Inmarsat immunity	35 dB (minimum)

<b>LNA Gain</b>	35 dB (typical)
-----------------	-----------------

### Gain at Zenith (90°)

GPS L1	4 dBi (minimum)
GPS L2	2.5 dBi (minimum)
GPS L5	0 dBi (minimum)

### Gain Roll-Off (from Zenith to Horizon)

GPS L1	13 dB (maximum)
GPS L2	12 dB (maximum)
GPS L5	12 dB (maximum)

<b>Noise Figure</b>	2 dB (typical)
---------------------	----------------

<b>VSWR</b>	≤ 2 : 1
-------------	---------

<b>L1-L2 Differential Propagation Delay</b>	7 ns (maximum)
---	----------------

<b>Nominal Impedance</b>	50 Ω
--------------------------	------

<b>Altitude</b>	9,000 m
-----------------	---------

## PHYSICAL AND ELECTRICAL

<b>Dimensions</b>	185 mm diameter <sup>1</sup> × 69 mm
-------------------	--------------------------------------

<b>Weight</b>	<530 g
---------------	--------

### Power

Input voltage	+4.5 to +18 VDC
Current	40 mA (typical)

<b>Connector</b>	N-Type
------------------	--------

## ENVIRONMENTAL

### Temperature

Operating (non-ATEX)	-40°C to +85°C
Operating (ATEX)	-40°C to +55°C
Storage	-55°C to +85°C

<b>Humidity</b>	MIL-STD 810G/CH1, Method 507.6, Procedure II
-----------------	---

<b>Vibration</b> (operating)	
Random	MIL-STD-810G/CH1, Method 514.7, Category 21 MIL-STD-810G/CH1, Method 514.7, Category 24 MIL-STD-810G/CH1, Method 514.7, Category 4
Sinusoidal	MIL-STD-810G/CH1, Method 528.1 IEC 60945, Section 8.7 IEC 60068-2-6, Test Fc

<b>Shock</b>	MIL-STD-810G/CH1, Method 516.7, Procedure I MIL-STD-810G/CH1, Method 516.7, Procedure II
--------------	---

<b>Bump</b>	IEC 60068-2-27, Test Ea, 25g IEC 60068-2-27, Test Ea, 100g, (Non-Operating)
-------------	---

<b>UV Protection</b>	MIL-STD-810G/CH1, Method 505.6, Procedure II
----------------------	---

<b>Salt Fog</b>	MIL-STD-810G/CH1, Method 509.6 IEC 60945 Section 8.12
-----------------	---

<b>Corrosive</b>	MIL-STD-810G/CH1, Method 518.2
------------------	-----------------------------------

<b>Water Resistance</b>	IPX6/IPX7 IEC 60945 Section 8.8
-------------------------	------------------------------------

## COMPLIANCE

### FCC

### IC


### CE

» RoHS 2011/65/EU

» R.E.D. 2014/53/EU

**REACH** EC 1907/2006

**ATEX** 2014/34/EU



For the most recent details of this product:  
[www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas](http://www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas)

## novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)  
or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

**Version 3** Specifications subject to change without notice.

©2016 NovAtel Inc. All rights reserved.

NovAtel and Pinwheel are registered trademarks of NovAtel Inc.

Any use of such marks by NovAtel Inc. is under license. Other trademarks and trade names are those of their respective owners.

Printed in Canada.

D20184 July 2016



1. Not including tape measure tab. Full diameter with tape measure tab is 195 mm.

